

AL'S HUBCAPS

516-742-6823

INSTALLATION FOR AH125

- 1) Clean all grease & dirt off each wheel. Use an alcohol based cleaner or glass cleaner as final cleaning agent. Scuffing the surface of the wheel is OK.
- 2) Take the chrome overlay & center cap out of their bag & lay down face up at each wheel to install on.



- 3) Make sure the wheel is clean & dry & then put a thin layer of *silicone on each overlay as shown in picture below. Be sure not to put too much near the outer edge or center cap area or it may ooze out. (Wipe off with an alcohol based cleaner or a prep sol any excess silicone).



** White Lines
Indicate Proper
Silicone Bead*

2 stripes on each spoke & around the pockets. Put a thin bead of silicone around the inner & outer perimeter.

4) Start with lining the overlay up with the valve hole & snap on 2 or 3 spokes then moving around clockwise 1 spoke at a time.



After all 9 spokes have snapped into place then put on the center cap. Look for alignment stand on back of cap to match with notch on wheel.



5) The silicone will take 6-8hrs. to dry but you need wait only 60 minutes till you drive the car away. We recommend if possible installing when the car can sit overnight or for several hours.

These chrome overlays are now permanently adhered to the wheel & need never come off even when changing tires.



*We recommend only GE Silicone II Clear to use on the overlay

WARRANTY INFORMATION & CHROME CARE

5 YR. LIMITED WARRANTY ON CHROME PLATING

YR. 1	100%	FULL SHIPPING
YR. 2	85%	RETURN SHIPPING
YR. 3	75%	RETURN SHIPPING
YR. 4	60%	RETURN SHIPPING
YR. 5	25%	RETURN SHIPPING

Thank you for purchasing the AH125 Chrome Overlay.

In order to take care of your newly chromed wheels here are some tips on cleaning.

- 1) Never use a brake cleaner to remove grease or brake film. The solvents are too strong & will most assuredly ruin any type of chrome finish.
- 2) Never use a cleaner or polish that contains any type of abrasives when cleaning a chrome wheel.
- 3) Never apply a wheel cleaner to a hot wheel. This will accelerate the active ingredients in the Ph level & may burn the chrome. Use a light spray of water to cool down wheel.
- 4) **WE RECOMMEND THE USE OF PH NUETRAL WHEEL CLEANERS ONLY.** This type of wheel cleaner is sold at most auto parts stores. Read label **For use on chrome or polished wheels.**
- 5) It is recommended that you use a wheel or car wax to protect the chrome & extend it's life..

You can ask your AH distributor or retailer for cleaning chemicals they might carry.